

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Shell Gadus S3 V220C 2
Product code : 001D8425
Unique Formula Identifier (UFI) : M420-Y0XE-H007-K465

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Automotive and industrial grease.
Uses advised against :
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : **Skeljungur hf**
Borgartún 26
105 Reykjavík
Telephone : +354 (444) 3000
Telefax :
Contact for Safety Data Sheet : msds@skeljungur.is

1.4 Emergency telephone number

: Emergency Line: Ambulance, Fire Department and Police, Phone 112
; Toxic Center of the National University Hospital Phone: 543-2222

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

Used grease may contain harmful impurities.
High-pressure injection under the skin may cause serious damage including local necrosis.
Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : A lubricating grease containing highly-refined mineral oils and additives.
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.
Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Reaction products of boric acid and lithium hydroxide	Not Assigned 701-475-3 01-2120772309-47	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361d specific concentration limit Repr. 2; H361d 7,8 %	1 - 2,9
Naphthenic acids, zinc salts, basic	84418-50-8 282-762-6 01-2119988500-34	Skin Sens. 1B; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411	1 - 1,49
Alkaryl amine	68411-46-1 270-128-1 01-2119491299-23	Repr. 2; H361f	0,1 - 2,9
Alkyl thiadiazole	Not Assigned 948-020-7 01-2120792779-28	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Acute Tox. 4; H332 Aquatic Chronic 4; H413	0 - 0,09

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Not expected to be a health hazard when used under normal conditions.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
- When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea. Not considered to be an inhalation hazard under normal conditions of use. Possible respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. No specific hazards under normal use conditions. Skin irritation signs and symptoms may include a burning sensation, redness, or swelling. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
- Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! Call a doctor or poison control center for guidance. Treat symptomatically. Notes to doctor/physician:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8	Revision Date: 29.05.2024	SDS Number: 800001006664	Date of last issue: 30.04.2024 Print Date 30.05.2024
----------------	------------------------------	-----------------------------	---

Treat symptomatically.
Call a doctor or poison control center for guidance.
High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.
Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Carbon monoxide may be evolved if incomplete combustion occurs.
Unidentified organic and inorganic compounds.

5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:
Avoid contact with skin and eyes.
6.1.2 For emergency responders:
Avoid contact with skin and eyes.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin.
Avoid inhaling vapour and/or mists.
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage stability : Keep container tightly closed and in a cool, well-ventilated place.
Use properly labeled and closable containers.
Store at ambient temperature.

Packaging material : Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
: Suitable material: For containers or container linings, use mild steel or high density polyethylene.
Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral	Not Assigned	TWA (Particles (mist))	1 mg/m ³	IS OEL
	Further information: When certain oils are heated, polycyclic aromatic hydrocarbons (PAH) are produced which can have a carcinogenic effect. Such substances can also be present in mineral oils., For mist from aqueous cutting fluid or suchlike, which may also include substances other than oils, the value is applied as a total content with regard to the non-aqueous part. For substances with individual lower limit values, these are applied.			
Oil mist, mineral		TWA (inhalable fraction)	5 mg/m ³	US. ACGIH Threshold Limit Values
Oil mist, mineral		TWA (Mist)	1 mg/m ³	IS OEL

Biological occupational exposure limits

No biological limit allocated.

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : Wear full face shield if splashes are likely to occur.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.
Protective clothing approved to EU Standard EN14605.

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.
Check with respiratory protective equipment suppliers.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

meeting EN14387 and EN143.

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Semi-solid at ambient temperature.

Colour : red

Odour : Slight hydrocarbon

Odour Threshold : Data not available

Dropping point : 240 °C
Method: IP 396

Melting / freezing point : Data not available

Initial boiling point and boiling range : Data not available

Flammability

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not classified as flammable but will burn.

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / upper flammability limit : Typical 10 %(V)

Lower explosion limit / Lower flammability limit : Typical 1 %(V)

Flash point : Not applicable

Auto-ignition temperature : > 320 °C

Decomposition temperature
Decomposition temperature : Data not available

pH : Not applicable

Viscosity
Viscosity, dynamic : Data not available

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

Viscosity, kinematic : Not applicable

Solubility(ies)
Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : log Pow: > 6
(based on information on similar products)

Vapour pressure : < 0,5 Pa (20 °C)
estimated value(s)

Relative density : 1,000 (15 °C)

Density : 1.000 kg/m³ (15,0 °C)
Method: Unspecified

Relative vapour density : > 1
estimated value(s)

Particle characteristics
Particle size : Data not available

9.2 Other information

Explosive properties : Classification Code: Not classified

Oxidizing properties : Data not available

Flammability (liquids) : Not classified as flammable but will burn.

Evaporation rate : Data not available

Conductivity : This material is not expected to be a static accumulator.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.
No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 (rat): > 5.000 mg/kg
Remarks: Low toxicity
Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Remarks: Low toxicity
Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks : Slightly irritating to skin.
Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks : Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks : For respiratory and skin sensitisation:
Not a sensitiser.
Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

Remarks : Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic
Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Product:

Remarks : Not a carcinogen.
Based on available data, the classification criteria are not met.

Remarks : Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies.
Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Effects on fertility :
Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

STOT - repeated exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal.
ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks : High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks : Slightly irritating to respiratory system.

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: LL/EL/IL50 > 100 mg/l
Practically non toxic:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates : Remarks: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 > 100 mg/l
Practically non toxic:
Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : Remarks: Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Based on available data, the classification criteria are not met.

Toxicity to microorganisms : Remarks: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: Not readily biodegradable.
Major constituents are inherently biodegradable, but contains components that may persist in the environment.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

12.4 Mobility in soil

Product:

Mobility : Remarks: Semi-solid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.
Causes physical fouling of aquatic organisms.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Waste, spills or used product is dangerous waste.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

nical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation
Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

Additional Information : Not dangerous goods - full transport

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

REACH : Not established.

TSCA : All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H361d : Suspected of damaging the unborn child.
H361f : Suspected of damaging fertility. (Causing atrophy of the testes)
H411 : Toxic to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version 6.8 Revision Date: 29.05.2024 SDS Number: 800001006664 Date of last issue: 30.04.2024
Print Date 30.05.2024

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
IS OEL	:	Iceland. Regulation on occupational exposure limits.
IS OEL / TWA	:	Time weighted average
IS OEL / TWA	:	Long term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

Exposure Scenario - Worker

300000000170	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery.- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC8b, PROC9 Environmental Release Categories: ERC4, ERC7, ATIEL-ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
General exposures (closed systems)Use in closed process, no likelihood of exposure	No other specific measures identified.
Initial factory fill of equip-	No other specific measures identified.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

mentUse in contained systemsUse in closed, continuous process with occasional controlled exposure-Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	
Initial factory fill of equipment(open systems)Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours
Operation of equipment containing engine oils and similar.Use in contained systemsUse in closed process, no likelihood of exposure	No other specific measures identified.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Equipment cleaning and maintenanceOperation is carried out at elevated temperature (> 20°C above ambient temperature).Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide extract ventilation to emission points when contact with warm (>50oC) product is likely. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

product.
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

Exposure Scenario - Worker

300000000171	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery.- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC8b, PROC20 Environmental Release Categories: ERC9a, ERC9b, ATIEL-ATC SPERC 9.Bp.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.
Operation of equipment containing engine oils and similar.Use in contained systemsUse in closed pro-	No other specific measures identified.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

cess, no likelihood of exposure	
Material transfersNon-dedicated facilityTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	Avoid carrying out activities involving exposure for more than 4 hours Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilitiesHeat and pressure transfer fluids in dispersive, professional use but closed systems	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product. The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment	
No exposure assessment presented for the environment.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
No exposure assessment presented for the environment.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

Exposure Scenario - Worker

300000000172	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use of lubricants and greases in open systems.- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC7, PROC8b, PROC9, PROC10, PROC13 Environmental Release Categories: ERC4, ATIEL-ATC SPERC 4.Ci.v1
Scope of process	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

Material transfersManual-Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	Avoid carrying out activities involving exposure for more than 1 hour.
Material transfersAutomated process with (semi) closed systems.Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilitiesTransfer of substance or preparation into small containers (dedicated filling line, including weighing)	Ensure material transfers are under containment or extract ventilation.
Roller, spreader, flow applicationRoller application or brushing	Provide extraction ventilation at points where emissions occur.
SprayingIndustrial spraying	Carry out in a vented booth or extracted enclosure. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Treatment by dipping and pouringTreatment of articles by dipping and pouring	Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

Exposure Scenario - Worker

300000000173	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use of lubricants and greases in open systems.- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC10, PROC11, PROC13 Environmental Release Categories: ERC8a, ERC8d, ATIEL-ATC SPERC 8.Cp.v1
Scope of process	Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for the environment.
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. Use suitable eye protection. Avoid direct eye contact with product, also via contamination on hands.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

Material transfersManual-Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	Avoid carrying out activities involving exposure for more than 1 hour.
Roller, spreader, flow applicationRoller application or brushing	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
SprayingNon industrial spraying	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 1 hour. Wear a respirator conforming to EN140 with Type A/P2 filter or better. Wear suitable coveralls to prevent exposure to the skin. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.
Treatment by dipping and pouringTreatment of articles by dipping and pouring	Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Equipment cleaning and maintenanceTransfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	Drain down system prior to equipment opening or maintenance. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Avoid carrying out activities involving exposure for more than 4 hours Retain drain downs in sealed storage pending disposal or for subsequent recycle.
Storage.Use in closed process, no likelihood of exposureUse in closed, continuous process with occasional controlled exposure	Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
No exposure assessment presented for the environment.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The Risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this	

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S3 V220C 2

Version
6.8

Revision Date:
29.05.2024

SDS Number:
800001006664

Date of last issue: 30.04.2024
Print Date 30.05.2024

product.
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Section 3.2 -Environment

No exposure assessment presented for the environment.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

No exposure assessment presented for the environment.