

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Rivolta S.B.C. Spray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Solvent-based cleaner

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS DENMARK ApS

Tuborg Boulevard 12, 3

2900 Hellerup

Telephone: +45 32 46 3000

Contact Person: HSE Advisor

E-mail: HSEASC@fuchs-oil.com

Telephone: +46 8 128 25 000

1.4 Emergency telephone number: +45 82 12 12 12

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Aerosols Category 1 H222: Extremely flammable aerosol.

H229: Pressurized container: May burst if heated.

Health Hazards

Aspiration Hazard Category 1 H304: May be fatal if swallowed and enters air-

ways.

Hazard summary

Physical Hazards: Flammable aerosol.

Health Hazards

Issue Date: 29.05.2015

Skin Contact: At long or repeated contact with skin it may cause dermatitis due to the

degreasing effect of the solvent.

Revision Date: 19.11.2020 Print date: 24.11.2020

SDS_DK - EN - 000000000600909802

Version: 3.1



Ingestion: If ingested, material may be aspirated into the lungs and cause chemical

pneumonitis. Treat appropriately.

2.2 Label Elements



Signal Words: Danger

Hazard Statement(s): H222: Extremely flammable aerosol.

H229: Pressurized container: May burst if heated.

Precautionary Statements

General information: P102: Keep out of reach of children.

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

Storage: P410+P412: Protect from sunlight. Do not expose to temperatures

exceeding 50 °C/122°F.

Supplemental label information

EUH066: Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular

hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the envi-

ronment without control.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture of components with propellant in aerosol can.

Chemical name	Identifier	Concentration *	REACH Registra- tion No.	Notes
Propane	EINECS: 200-827-9	0% - <50,00%	01-2119486944-21	
Butane	EINECS: 203-448-7	0% - <50,00%	01-2119474691-32	
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	0% - <50,00%	01-2119485395-27	
Ethanol	EINECS: 200-578-6	20,00% - <50,00%	01-2119457610-43	
Hydrocarbons, low viscous	EC: 927-241-2	10,00% - <20,00%	01-2119471843-32	
Isopropyl alcohol	EINECS: 200-661-7	1,00% - <5,00%	01-2119457558-25	

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020 SDS DK - EN - 000000000600909802

Revision Date: 19.11.2020 Version: 3.1
Print date: 24.11.2020

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



Classification

Chemical name	Identifier	Classification	
Propane	EINECS: 200-827-9	CLP:	Flam. Gas 1A;H220, Press. Gas H280
Butane	EINECS: 203-448-7	CLP:	Flam. Gas 1A;H220, Press. Gas H280
Isobutane (<0,1% 1,3-butadiene)	EINECS: 200-857-2	CLP:	Flam. Gas 1A;H220, Press. Gas H280
Ethanol	EINECS: 200-578-6	CLP:	Flam. Liq. 2;H225, Eye Irrit. 2;H319
Hydrocarbons, low viscous	EC: 927-241-2	CLP:	Flam. Liq. 3;H226, Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 3;H412
Isopropyl alcohol	EINECS: 200-661-7	CLP:	Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336

CLP: Regulation No. 1272/2008.

specific concentration limit

Chemical name		specific concentra- tion limit		Category	Hazard state- ments
Ethanol	EINECS: 200-578-6	>= 50 %	Serious eye irritation	2	H319

For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and

delayed:

If ingested, material may be aspirated into the lungs and cause chemical

pneumonitis. Treat appropriately. Dizziness Freeze burns

4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a pro-

tected location. Move containers from fire area if you can do so without risk.

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020 SDS_DK - EN - 00000000600909802

Revision Date: 19.11.2020 Version: 3.1
Print date: 24.11.2020



5.1 Extinguishing media

Suitable extinguishing me-

dia:

CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant add-

ed

Unsuitable extinguishing

media:

Water with a full water jet.

5.2 Special hazards arising from the substance or mixture:

Danger of explosion with aerosol cans.

5.3 Advice for firefighters

Special fire fighting proce-

dures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter

drains.

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep away from sources of ignition - No smoking.

6.2 Environmental Precautions:

Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas.

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020 SDS_DK - EN - 00000000600909802



7.2 Conditions for safe storage, including any incompatibili-

ties:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations concerning handling and storage of waterpolluting products have to be followed. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away

from heat/sparks/hot surfaces. - No smoking.

7.3 Specific end use(s): Not applicable

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source	
Ethanol	GV	1.000 ppm 1.900 mg/m	Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)	
Propane	GV	1.000 ppm 1.800 mg/m	Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)	
Butane	GV	500 ppm 1.200 mg/m	Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)	
Isopropyl alcohol	GV	200 ppm	Denmark. Danish List of Organic Solvents, Danish Labor Inspectorate (08 2007)	
Isopropyl alcohol	GV	200 ppm 490 mg/m	Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3, as amended (12 2011)	

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Wash hands before breaks and after work. Use personal protective equip-

ment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be ad-

hered to inhandling the chemicals or the mineral oil products.

Eye/face protection: Avoid contact with skin and eyes. Goggles/face shield are recommended. If

risk of splashing, wear safety goggles or face shield.

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020

SDS_DK - EN - 000000000600909802



Skin protection

Hand Protection: Material: Nitrile butyl rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufactur-

er of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser pock-

ets. Wear suitable protective clothing.

Respiratory Protection: Do not breathe dust/fume/gas/mist/vapors/spray. Provide adequate ventila-

tion. In case of inadequate ventilation wear respiratory protection. Filter

AX/P2.

Thermal hazards: Not known.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

> handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated foot-

wear that cannot be cleaned.

Environmental Controls: No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Aerosols Form: Aerosols Color: Colorless Odor: Characteristic

Odor Threshold: Not applicable for mixtures

pH: substance/mixture is non-soluble (in water)

Freezing point: Not applicable for mixtures

Boiling Point: 78 °C

Flash Point: < -60 °C (DIN EN ISO 2719) **Evaporation Rate:** Not applicable for mixtures

Flammability (solid, gas): Value not relevant for classification Flammability Limit - Upper (%)-: Value not relevant for classification Flammability Limit - Lower (%)-: Value not relevant for classification

Vapor pressure: Not applicable for mixtures Vapor density (air=1): Not applicable for mixtures Density: 0,82 g/cm3 (15 °C) (DIN 51757)

Solubility(ies)

Solubility in Water: partly soluble Solubility (other): No data available.

Issue Date: 29.05.2015 Revision Date: 19.11.2020

SDS_DK - EN - 000000000600909802

Version: 3.1 Print date: 24.11.2020



Partition coefficient (n-octanol/water): Not applicable for mixtures

Autoignition Temperature:

Decomposition Temperature:

Value not relevant for classification

9.2 Other information No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity: Stable under normal use conditions.

10.2 Chemical Stability: Stable under normal use conditions.

10.3 Possibility of hazardous

reactions:

Stable under normal use conditions.

10.4 Conditions to avoid: Stable under normal use conditions.

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids. Strong bases.

10.6 Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and oth-

er toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Ethanol

LD 50 (Rat): > 6.200 mg/kg

Hydrocarbons, low vis-

cous

LD 50 (Rat): > 5.001 mg/kg (OECD 401)

Isopropyl alcohol LD 50 (Rat): 4.570 mg/kg

Dermal

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Ethanol

LD 50 (Rabbit): > 20.000 mg/kg (OECD 402)

Hydrocarbons, low vis-

cous

LD 50 (Rabbit): > 5.001 mg/kg (OECD 402)

Isopropyl alcohol LD 50 (Rabbit): 13.400 mg/kg

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020 SDS_DK - EN - 00000000600909802

evision Date: 19.11.2020 Version: 3.1



Inhalation **Product:**

Not classified for acute toxicity based on available data.

Specified substance(s)

Butane LC 50 (Rat, 4 h): 658 mg/l

Gas

Isopropyl alcohol LC 50 (Rat, 4 h): 30 mg/l

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

Hydrocarbons, low vis-**OECD 404**

Prolonged or repeated contact: cous

Slightly irritating.

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not

Respiratory sensitizer: Based on available data, the classification criteria

are not met.

Specified substance(s) Hydrocarbons, low vis-

No sensitizing effect (guinea pig); OECD 406 cous

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other adverse effects: No data available.

Issue Date: 29.05.2015 Revision Date: 19.11.2020

SDS_DK - EN - 000000000600909802

Version: 3.1 Print date: 24.11.2020

8/12



SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Propane LC 50 (Fish, 96 h): > 1.000 mg/l

Isobutane (<0,1% 1,3-

butadiene)

LC 50 (Fish, 96 h): 28 mg/l

Ethanol LC 50 (Fish, 96 h): > 2.000 mg/l (OECD 203)

Hydrocarbons, low vis-

cous

LC 50 (Fish, 96 h): 10 - 30 mg/l

Isopropyl alcohol LC 50 (Fish, 96 h): 9.640 mg/l

Aquatic Invertebrates Specified substance(s)

Isobutane (<0,1% 1,3-

butadiene)

EC 50 (Water Flea, 48 h): 16,3 mg/l

Ethanol LC 50 (Water Flea, 48 h): 5.012 mg/l

Hydrocarbons, low vis-

cous

EC 50 (Water Flea, 48 h): 22 - 46 mg/l

Isopropyl alcohol LC 50 (48 h): 1.400 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are not met.

Aquatic Invertebrates Specified substance(s)

Ethanol NOEC (Water Flea, 10 d): 9,6 mg/l

Toxicity to Aquatic Plants Specified substance(s)

Isobutane (<0,1% 1,3-

butadiene)

EC 50 (Alga, 72 h): 8,6 mg/l

Ethanol EC 50 (Alga, 72 h): 275 mg/l (OECD 201)

NOEC (Alga, 7 d): 208 mg/l (OECD 201)

Hydrocarbons, low vis-

cous

EC 50 (Alga, 72 h): > 1.000 mg/l

Isopropyl alcohol LC 50 (Alga, 72 h): > 100 mg/l

12.2 Persistence and Degradability

SDS_DK - EN - 000000000600909802

Biodegradation

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020

Revision Date: 19.11.2020 Version: 3.1

9/12



Product: Not applicable for mixtures

Specified substance(s)

Ethanol > 70 % (5 d, OECD 301D) Readily biodegradable

Hydrocarbons, low vis-

cous

89 % (28 d) The product is easily biodegradable.

12.3 Bioaccumulative potential

Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB

assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects: No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

European Waste Codes

16 05 04*: Gases in pressure containers (including halons) containing

dangerous substances.

SECTION 14: Transport information

ADR/RID

14.1 UN Number: UN 195014.2 UN Proper Shipping Name: AEROSOLS

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.1
Hazard No. (ADR): Tunnel restriction code: (D)

14.4 Packing Group:

14.5 Environmental hazards: –
14.6 Special precautions for user: –

ADN

14.6 Special precautions for user: -

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020

SDS_DK - EN - 000000000600909802

Revision Date: 19.11.2020 Version: 3.1

10/12



IMDG

14.1 UN Number: UN 1950 14.2 UN Proper Shipping Name: **AEROSOLS**

14.3 Transport Hazard Class(es)

2.1 Class: Label(s): 2.1 EmS No.: F-D, S-U

14.3 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user:

IATA

14.1 UN Number: UN 1950

Aerosols, flammable 14.2 Proper Shipping Name:

14.3 Transport Hazard Class(es):

Class: 2.1 Label(s): 2.1 14.4 Packing Group: 14.5 Environmental hazards: 14.6 Special precautions for user:

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer: none

Regulation (EC) No. 850/2004 on persistent organic pollutants: none

15.2 Chemical safety as-

sessment:

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor

H229 Pressurized container: May burst if heated.

Contains gas under pressure; may explode if heated. H280

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Other information: The classification complies with the current EU lists; however, it has been

Issue Date: 29.05.2015 Revision Date: 19.11.2020

SDS_DK - EN - 000000000600909802

Version: 3.1 Print date: 24.11.2020



supplemented with expert literature information and information provided by/about our company. It was derived from the test data and/or the application of the conventional method.

Revision Date: Disclaimer:

19.11.2020

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.

Issue Date: 29.05.2015 Revision Date: 19.11.2020 Print date: 24.11.2020