



TDS

## VENOL SÄGEÖL 100

Application:

Mineral oil for lubrication of sawmills and chainsaws. The use of adhesive and anti-wear additives ensures high durability of the oil film and reduces the wear of cooperating elements. It is miscible with other brand oils of this type.

*Specifications and Standards:*

*Viscosity class according to ISO VG: 100*

*A list of typical physicochemical properties*

<b>Venol SÄGEÖL 100</b>	<b>Typical values</b>
Kinematic viscosity at 400 C mm <sup>2</sup> / s	98
Viscosity index	95
Pour point °C	-15
Flash-point °C	235

Venol Motor Oil GmbH  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl



**Venol Motor Oil GmbH**  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl

[www.venol.de](http://www.venol.de)