



## TDS

### VENOL SEMISYNTHETIC DIESEL TRUCK XHPD CI4 CG4 10W40

#### Application:

High quality motor oil based on synthetic base stocks. It delivers optimum, long lasting wear protection for heavily loaded diesel engines with or without turbocharging. It is especially designed for powerfull vehicles working in cycles of big individual mileage. It is especially recommended for semi-trailer trucks. It guarantees easy start up in low temperatures. It can be used in vehicles equipped with catalytic converter systems. Ready to be mixed with other branded oil of this kind.

#### Specifications:

SAE: 10W40  
API: CI4 CG4  
ACEA: E5/E7

Meets the requirements: VOLVO VDS-3, MAN 3277, RENAULT RLD, DAF HP2,  
MB 228.5

VENOL SEMISYNTHETIC DIESEL TRUCK XHPD CI4 CG4 10W40	Typical values
Kinematic viscosity at 100 <sup>0</sup> C mm <sup>2</sup> /s	14,9
Viscosity index	140
TBN mg KOH/g	11,0
Pour point <sup>0</sup> C, max <sup>0</sup> C	-36
Flash point <sup>0</sup> C	238
Sulfated ash %weight	1,1

Venol Motor Oil GmbH  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

Geschäftsführer: Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl



**Venol Motor Oil GmbH**  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl

[www.venol.de](http://www.venol.de)