



## TDS

### A.M.G. VENOL BRAKE FLUID SUPER ACTIVE DOT-4

#### Specifications:

A.M.G. VENOL BRAKE FLUID DOT-4 is a modern brake fluid of high quality and boiling temperature of over 230°C. For use in clutch systems, disc brake systems, and drum brake systems of passenger cars, trucks, buses, and motorcycles. Recommended particularly for vehicles with brake systems and clutch systems under severe strain. Using brake fluid increases braking safety, provides perfect anti-corrosion protection, prevents swelling of rubber elements, and extends service life of the brake system. Shows very good functional properties.

**Application:** Use according to the operation and maintenance manual of the vehicle, in environment temperature from -50°C to + 50°C. May be mixed with other DOT-4 fluids. Change brake fluid every two years or after mileage of 40 thousands km.

A.M.G. VENOL BRAKE FLUID SUPER ACTIVE DOT-4	Typical values
Boiling temperature	230°C
Minimum boiling temperature of dampened liquid	155°C
pH	7,0-11,5
Thermal stability	+/- 3°C
Chemical stability	+/- 3°C
Galvanized steel	0,2 to -0,2
steel	0,2 to -0,2
aluminium	0,1 to -0,1
cast iron	0,2 to -0,2
brass	0,4 to -0,4
copper	0,4 to -0,4

Venol Motor Oil GmbH  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl



**Venol Motor Oil GmbH**  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl

[www.venol.de](http://www.venol.de)