

Product Information VG.30.01

08-02-2022

VatOil LHM Plus

Description

LHM Plus is a special mineral hydraulic system fluid. It is based on high quality base oils with an extremely high viscosity index. This gives LHM Plus the following properties:

- Very low pouring point
- Does not affect oil-proof seal
- Strong foam-inhibiting properties

Application

LHM Plus is suitable for hydro-pneumatic systems of Citroën and all other automotive applications where a LHM-liquid is prescribed. Always check the product recommendation database for the right application.

Specifications

PSA B71 2710

Typicals

| | |
|--------------------------------------|-------|
| Colour | GROEN |
| Density at 15 °C, kg/l | 0,837 |
| Viscosity -40 °C, mm ² /s | 1150 |
| Viscosity 40 °C, mm ² /s | 18,60 |
| Viscosity 100 °C, mm ² /s | 6,20 |
| Viscosity Index | 330 |
| Flash Point COC, °C | 125 |
| Pour Point, °C | -50 |
| Pour Point, °C | <-60 |
| Acid number, mgKOH/g | 0,05 |
| Boiling Point (reflux) , °C | 291 |
| Analinepoint, °C | 95 |

Available packagings



50001
1 L bottle



50002
20 L can



50343
60 L drum



50344
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.