



TDS

GARTEN SG/CE 30

Mineral motor oil designed for four-stroke engines in gardening machinery, such as: lawn mowers, trimmers, brush cutters. Recommended also for engines in cultivators, micro tractors, rototillers, plows and other auxiliary appliances. Can be mixed with other branded motor oils.

SAE 30 API SG/CE

GARTEN SG/CE30	Typical values
Kinematic Viscosity at 100°C, mm ² /s	11,00
Viscosity index, min	95
TBN (mg KOH/G)	4,5
Pour point, max °C	-15
Flash point, min °C	210

Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl



Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl

www.venol.de