



TDS

VENOL ATF VI DEX VI RED

1.PRODUCT CHARACTERISTICS:

Gear oil intended for use in 6-stage automatic gearboxes of passenger cars and trucks, in which the manufacturer recommends the use of Dexron VI oil. Provides excellent lubricating properties, high thermal and oxidative stability. Ready to be mixed with other branded gear oils of this kind.

2. MEETS THE REQUIREMENTS:

GM DEXRON III H/II D; FORD MERCON LV; MB 236.41; HYUNDAI/KIA SP-IV, SP-II, SP-III, SP-IV/ SPH-IV; TOYOTA ATF TYPE WS, T-III, T-IV; ZF M1375; NISSAN/INFINITI MATIC S, K, J, D; ALLISON C-4; HONDA ATF Z1; DIMLER CHRYSLER ATF +3,+4; VW/AUDI G 055 540 A2; BMW 83 22 9 407 858/83 22 9 407 859; MITSUBISHI DIAMOND ATF SP II, SP III; JALOS LASO 1A; LEXUS ATF TYPE WS/T-III/T-IV; ACURA DW1,ATF Z1

3. TECHNICAL REQUIREMENTS:

VENOL ATF VI DEX VI RED	Description or requirement
Kinematic viscosity at 100 ⁰ C mm ² /s	7,0
Viscosity index	165
Pour point ⁰ C, max ⁰ C	-42
Flash point ⁰ C	220

Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl



Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl

www.venol.de