



TDS
VENOL GEAR GL-4 85W-90

Characteristic:

Mineral oil for vehicle transmission gears that provides excellent lubricating and anti-rust properties, high oxidization resistance and high load carrying capacity. Thanks to the AW and EP additives, GL-4 85W-90 oil provides very good anti-wear and antifricition properties. The oil is used to lubricate back axles and transmission gears of the vehicles working under severe conditions.

Specifications:

Viscosity grade: SAE 85W/90

Quality class: API :GL-4

Meets the requirements:

MAN 342 Type M1, Mercedes Benz 235.0, MIL-L-2105D

Voith 3.325-339, Volvo 97310, DAF

VENOL GL-4 85W/90	Typical values
Viscosity at 100°C, mm ² /s	14,5
Viscosity index, min	120
TAN, min (mg KOH/g)	0,2
Pour point, max °C	-27
Flash point, min °C	200

Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl



Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl

www.venol.de



Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl

www.venol.de