



TDS

VENOL Gear Semisynthetic GL-4 75W/90

High quality semisynthetic gear oil for heavily and medium-loaded transmissions, back axles, as well as gears in passenger cars, commercial vehicles, trucks, buses and other modes of transport operating in severe conditions, when using oil of similar quality class is recommended by the manufacturer. Guarantees excellent performance under all driving conditions. Can be mixed with other branded gear oils.

Characteristic:

Viscosity grade: SAE : 75W/90

Quality class: API: GL-4

Meets the requirements: MIL-L-2105

VENOL Gear GL-4 75W/90	Typical physico-chemical attributes
Viscosity at 100°C, mm ² /s	14,5
Viscosity index, min	130
Pour point, max °C	-30
Flash point, min °C	200
TAN mg KOH/g	0,2

Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl



Venol Motor Oil GmbH
Litauische Str. 43
15234 Frankfurt Oder
Ust-Id- Nr DE-319472195
ST-NR 061/121/03730
HRB 93818

Geschäftsführer: Maciej Filip Gostynski
Bankverbindung: DE 38 4401 0046 0408 0114 61
BIC: PBNKDEFF
Tel. 0049 335 401 44 01
venol@venol.pl

www.venol.de