

Product Information VG.20.07

10-02-2022

VatOil SynMat DCT

Description

SynMat DCT is a synthetic transmission oil for dual clutch transmissions. This specially formulated product with superior characteristics has the following properties:

- Excellent oxidation stability
- Very good lubrication properties
- Outstanding resistance to wear
- High resistance against foaming
- Very low pouring point
- Excellent shear stability

Application

SynMat DCT has been specially developed for the new generation of High Tech DSG transmissions as used in a range of VAG models, along with an increasing number of models by other makes. Always consult the VatOil product advisory database for optimal use.

Specifications

BMW DCTF-1 / DCTF-1+ / LT-5

BorgWarner

Bugatti Veyron

Chrysler 68044345 EA & GA

Ferrari TF DCT-F3

Ford WSS-M2C936-A / WSS-M2C218-A1

Hyundai/Kia

MB 236.21 / 236.24 / 236.25 / 239.21

Mitsubishi Dia-Queen SSTF-1

Porsche/ZF FFL-3

PSA 9734 S2

Renault EDC

Volvo 1161838 / 1161839

VW G 052 182 / G 052 529 / G 055 529

VW G 052 536 / G 055 536

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,848
Viscosity 40 °C, mm ² /s	34,00
Viscosity 100 °C, mm ² /s	7,17
Viscosity Index	183
Flash Point COC, °C	201
Pour Point, °C	-48
Acid number, mgKOH/g	1,29
Brookfield -40°C, mPa.s	11400

Available packagings50266
1 L bottle50207
20 L can50331
60 L drum50332
200 L drum