

#### **TDS**

# **VENOL LOGISTIC TRUCK XHPD CI4/CH4 15W40**

## Characteristic:

High quality motor oil based on specially selected mineral base stocks. Delivers optimum, long-lasting wear protection for heavily loaded diesel engines with or without turbochargers. Designed particularly for powerful vehicles working in cycles of big individual mileage. Especially recommended for semi-trailers. Guarantees easy start up in low temperatures. Can be used in vehicles equipped with catalytic converter systems. Can be mixed with other branded motor oils.

### Specifications:

Viscosity grade: SAE 15W40 Quality class: API : CI4/CH4 Quality class: ACEA: E7

#### **VENOL LOGISTIC TRUCK XHPD CI4/CH4 15W40**

Meets the requirements: CAT ECF-1, VOLVO VDS 3, MAN 3275, Renault RLD2, MB228.3

VENOL LOGISTIC TRUCK XHPD CI4/CH4 15W/40	Typical physico-chemical attributs
Kinematic Viscosity at 1000 C, mm2/s	14,5
Viskosity index	130
TBN, min ( mg KOH/g)	10,2
Pour point, max °C	-31
Flash point, min °C	230



Venol Motor Oil GmbH Litauische Str. 43 15234 Frankfurt Oder Ust-Id- Nr DE-319472195 ST-NR 061/121/03730 HRB 93818

Geschäftsführer: Maciej Filip Gostynski Bankverbindung: DE 38 4401 0046 0408 0114 61 BIC: PBNKDEFF Tel. 0049 335 401 44 01 venol@venol.pl



Venol Motor Oil GmbH Litauische Str. 43 15234 Frankfurt Oder Ust-Id- Nr DE-319472195 ST-NR 061/121/03730 HRB 93818

Geschäftsführer: Maciej Filip Gostynski Bankverbindung: DE 38 4401 0046 0408 0114 61 BIC: PBNKDEFF Tel. 0049 335 401 44 01 venol@venol.pl