

# Sales Specification

1 of 1

## Acetic Acid

### Food Grade E 260, 80 %

CAS-No. 64-19-7

<u>Characteristic</u>	<u>Limit</u>	<u>Unit</u>	<u>Method</u>
Acetic Acid	79.5 – 80.5	% (w/w)	ISO 753/2
Platinum/Cobalt Color (Hazen/APHA Color)	max. 5		DIN EN 1557 / DIN ISO 6271 / ASTM D 1209 / ASTM 5386
Permanganate Time / Oxidizable Impurities	min. 2	hours	FCC, 12 <sup>th</sup> ed., Monograph Specifications
Density at 20 °C <sup>1)</sup>	1.069 – 1.071	g/cm <sup>3</sup>	DIN 51 757, Method D
Appearance	Clear and free		Visual Examination

#### Remarks:

<sup>1)</sup> Product conforms to limit, but test is not routinely performed.

Acetic Acid, Food Grade E260 80 % is produced by dilution of Acetic Acid, Food Grade E260 99/100 % with drinking water. Further inspection characteristics can be derived from the Celanese Sales Specification for Acetic Acid, Food Grade E260 99/100 %.

The product meets the requirements of European Community Regulation (EC) 178/2002, Directive 2012/231/EC (E 260, Acetic Acid), Regulation (EC) 852/2004 (HACCP-based) and Food Chemicals Codex 12<sup>th</sup> Ed.

Product-No.	50000990	Version-No.	7
		Released	June 1, 2020

Test methods used are available upon request. Contact your Sales Support for copies.  
 For additional physical properties, see Celanese Product Description and Handling Guide.

**Celanese Corporation Headquarters**  
 222 W. Las Colinas Blvd., Suite 900N  
 Irving, Texas 75039, United States  
 Phone +1-972-443-4000

**Celanese Sales Germany GmbH**  
 Am Unisys-Park 1  
 65843 Sulzbach, Deutschland / Germany  
 Tel: +49 (0) 69 45009 0

*The information contained in this publication is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not be construed as warranting or guaranteeing specific properties of the products described or their suitability for a particular application. User is solely responsible for determining the suitability of the products for the intended purpose. To the best of our knowledge the information in this publication is accurate; however we do not assume any liability whatsoever for the accuracy and completeness of such information. We strongly recommend that users seek and adhere to our current instructions for handling these products, and to entrust the handling of such products to adequately trained personnel only. Please adhere to the instructions and information contained in the corresponding Material Safety Data Sheets (MSDS) before attempting to process our products. Any existing industrial property rights must be observed. User is solely responsible for investigating and checking the regulatory approval status.*